



**KEYSTONE**  
WASTE SOLUTIONS LLC



# Roll-Off Bathtub Style

## 10-40 Yard Bathtubs



### Container Specifications:

- 3" x 3.5lb Channel x-member on 18" centers
- 4" x 3" x 3/16" Structural tubing top rails
- 1" Hook plate
- 1 1/4" Cable hook
- 8" x 8" Rear wheel w/ greasable axles
- 4" x 6" Front wheels w/ greasable axles
- (3) Heavy duty greasable hinges (30 yard height and above)
- (3) Cam style latches (30 yard height and above)
- 4" x 3" Structural tubing door frame with center channel
- 3/16" Formed front and rear corner post
- V-style tarp hooks on fronts/sides/doors

	Standard	Heavy duty
Floor sheet	3/16"	1/4"
Main rails	3/16"	1/4"
Side walls/front	10ga	7ga

### Other Options:

- Tarp, lid and roof options
- Hook lift, dual hook and other skid compatible options
- Other sizes/yardage/specifications available on request

### Features and Benefits:

- Smooth side nestable design reduces freight cost and allow adequate space for branding with no interference of vertical channels.
- Front design protects driver from exposure to sharp edges, allows for easy cable placement, and provides added strength to the front of the containers.
- Front and rear door corners are ground smooth to prevent tarp damage.
- Front corner wraps installed and solid welded to prevent separation of side walls and front.
- Exterior walls are welded solid exterior and skip welded inside preventing premature failures causing expensive repair.
- Interior top rails are welded solid to prevent premature rusting and rust streaking on the outside of the container.
- Cam latch, safety chains, and greasable 1/2" plate hinges with 1 1/4" hinge pins ensure door securement.
- Front roller and rail rollers with greasable pins to prevent premature wearing of critical parts
- Containers fully primed with exterior painted including bottom from rails outward to prevent premature rusting

